

Industry Leading Business Solutions



TS-200 2D

PROFESSIONAL TABLE
BARCODE SCANNER






TS-200

2D TABLE BARCODE SCANNER



Product Size



SPECIFICATIONS

Performance Parameters

Light Source:	Red LED
Supported:	1D: Codabar, Code 39, Code 32, Interleaved 2 of 5, NEC 2 of 5, Code 93, Straight 2 of 5, Industrial, Straight 2 of 5 IATA, Matrix 2 of 5, Code 11, Code 128, ISBT 128, GS1-128, UPC-A, UPC-E0, UPC-E1, EAN/JAN-13, EAN/JAN-8, ISBN, MSI, GS1 DataBar-Omnidirectional, GS1 DataBar Limited, GS1 DataBar Expanded. 2D: PDF417, QR code, DataMatrix, Aztec Code, China Post, HongKong 2 of 5, Korea Post, Han Xin code, Maxi code, Micro PDF417, GS1 Composite coders, Codablock A, Codablock F.
System compatibility:	Linux, Android, Windows XP/7/8/10
Scan Range:	10-160mm(EAN 13 13mil, PCS=90%)
Print Contrast:	20% minimum reflective difference
Minimum recognition accuracy:	Code 39 4mil
Motion Tolerance:	4 meters/second
Scan Mode:	Automatic Induction Scanning
Image (Pixels):	640 pixels(H) x 480 pixels(V)
Man-machine Interaction:	Indicator light: Blue light power indicator; Blue light flashing code reading prompt, Buzzer: start prompt, read code prompt.
Recognition angle range:	Turn $\pm 360^\circ$, Elevation $\pm 65^\circ$, Declination $\pm 65^\circ$
Interface:	USB(Drive-Free), RS232, USB-COM

Physical Parameters

Dimensions:	96mm*108mm*150mm
Weight:	294.4g
Material:	ABS+PC
Cable Length:	2M
Shock Resistance:	Withstands multiple times 1.5 meters drops to concrete

Environmental Parameters

Operating Temperature:	0°C~50°C
Storage Temperature:	-40°C~70°C
Relative Humidity:	0% ~95% RH (non-condensing/non-freezing)

Electronic Parameters

Working Voltage:	DC5V \pm 5%
Current:	Standby Current 190mA; Working Current 240mA

PRODUCT FEATURES

- New decoding chip, interpretation of various 1D & 2D barcode
- Professional technology, can scan WeChat/alipay bar code
- Plug and play, simple setup, fast use
- Power indicator on the bottom
- Wire life more durable

