

AO-PR-1001

PR-250 THERMAL PRINTER



**Thermal Receipt Printer 80mm,
(USB+LAN+Serial) 250mm/s**

- HIGH SPEED OF PRINTING UP TO 250MM/S
- FIRMWARE ONLINE UPDATING AVAILABLE
- 2D BARCODE PRINTING SUPPORT
- FEAT. DATA LOSS PREVENTION



PR-250 THERMAL PRINTER



MODEL:	PR-250 Thermal Printer
Printing method	Thermal Line
PAPER roll diameter	80mm (MAX)
Paper width	79.5±0.5mm
Print width	48mm / 72mm
Column capacity / Resolution	576 dots/line / 8 dots/mm(203dpi)
Printing speed	250mm/s
Interface	USB+LAN+Serial
Auto cutter	Partial
Cutter life	1.5 million cuts
Printer head life	150km

Fonts Symbology	
Character size	Font A: 12*24, Font B: 9*17, CHN: 24*24
Character /Line	48 (Font A) / 64 (Font B) / 24 (CHN)
1D Barcode	UPC-A / UPC-E / JAN13(EAN13) / JAN8(EAN8) / CODE39 / ITF25 / CODEBAR / CODE93 / CODE128
2D Barcode	PDF417 / QRCODE / Data Matrix
Input buffer	8K Bytes (circular buffer)
NV Flash	512Kbytes

Power	
Power adapter	Input: 100-240V~50/60Hz 1.5A MAX, Output: 24V 2A, 48W
Power source	DC 24V±10%, 2A
Cash drawer	DC 24V/1 A, 6 PIN RJ-11 socket

Physical characteristics	
Weight	1850g
Dimensions	200*150*139 mm (L*W*H)

Environmental Requirements	
Work environment	Temperature (0 ~ 50°C) humidity (10 ~ 80%)
Storage environment	Temperature (-20 ~ 60°C) humidity (10 ~ 90%)

Reliability	
Printer head life	150 KM

Software	
Emulation	ESC/POS
Driver	Windows / Linux / Mac
Utility	Windows
SDK	iOS / Android / Windows

POWER

SERIAL

ETHERNET

USB

D/K

