



AO-SC-1002

# TS-200

## TABLE SCANNER



NEW DECODING CHIP,  
INTERPRETATION OF VARIOUS  
1D & 2D BARCODE  
PROFESSIONAL TECHNOLOGY,  
CAN SCAN WECHAT/ALIPAY  
BAR CODE  
PLUG AND PLAY, SIMPLE SETUP,  
FAST USE  
POWER INDICATOR ON THE  
BOTTOM  
WIRE LIFE MORE DURABLE

# TS-200

# TABLE SCANNER

**Light Source:** Red LED

**Supported Symbologies:** 1D: Codabar, Code 39, Code 32, Interleaved 2 of 5, NEC 2 of 5, Code 93, Straight 2 of 5, Industrial, Straight 2 of 5 IATA, Matrix 2 of 5, Code 11, Code 128, ISBT 128, GS1-128, UPC-A, UPC-E0, UPC-E1, EAN/JAN-13, EAN/JAN-8, ISBN, MSI, GS1 DataBar-Omnidirectional, GS1 DataBar Limited, GS1 DataBar Expanded. 2D: PDF417, QR code, DataMatrix, Aztec Code, China Post, HongKong 2 of 5, Korea Post, Han Xin code, Maxi code, Micro PDF417, GS1 Composite coders, Codablock A, Codablock F.

**System compatibility:** Linux, Android, Windows XP/7/8/10

**Scan Range:** 10-160mm(EAN 13 13mil, PCS=90%)

**Print Contrast:** 20% minimum reflective difference

**Minimum recognition accuracy:** Code 39 4mil

**Motion Tolerance:** 4 meters/second

**Scan Mode:** Automatic Induction Scanning

**Image (Pixels):** 640 pixels(H) x 480 pixels(V)

**Man-machine Interaction:** Indicator light: Blue light power indicator;  
Blue light flashing code reading prompt,  
Buzzer: start prompt, read code prompt.

**Recognition angle range:** Turn  $\pm 360^\circ$ , Elevation  $\pm 65^\circ$ , Declination  $\pm 65^\circ$

**Interface:** USB(Drive-Free), RS232, USB-COM

## Physical Parameters

**Dimensions:** 96mm\*108mm\*150mm

**Weight:** 294.4g

**Material:** ABS+PC

**Cable Length:** 2M

**Shock Resistance:** Withstands multiple times 1.5 meters drops to concrete

## Electronic Parameters

**Working Voltage:** DC5V $\pm 5\%$

**Current:** Standby Current 190mA; Working Current 240mA

## Environmental Parameters

**Operating Temperature:** 0°C~50°C

**Storage Temperature:** -40°C~70°C

**Relative Humidity:** 0% ~95% RH (non-condensing/non-freezing)



## AO-SC-1002