



A0-A0-1000

ALLMAX-300

Professional
All-in-One
Terminal



15" TOUCHSCREEN

AUXILIARY 9.7 DISPLAY

MODERN AND STYLISH DESIGN

FAST AND EASY INSTALLATION

ALUMINUM ALLY BRACKET

CABLE COVER FOR I/O

MULTIPLE I/O

ALLMAX-300

Professional All-in-One Terminal



Processor

Intel® Celeron® J6412, Quad-core,
clock speed 2.00 GHz, up to 2.60GHz,
TDP 10W

Memory Storage OS

4GB, DDR3
128 SSD

Compatible with: Windows 7, windows
8.1, windows 10, POS Ready7

DISPLAY Type Resolution Touchscreen

15" TFT LED Backlight

1024*768

Projective Capacitive Touch Screen

INTERFACE Display

1*VGA(J1900), 1*HDMI (i3 &
i5)&1*VGA(J1900, i3, i5)

USB Serial LAN

6*USB(J1900), 4*USB(i3, i5)
2*COM

Audio Power DC-IN

1*Gigabit Ethernet, RJ45

1*Line-out, 1*Mic-in

Input AC 100~240V/50~60hz, Output
DC12V/5A

POWER Power Supply

Adaptor 12V, 5A

OPTIONS & PERIPHERALS Customer Display Wall Mount Kit

NONE

VESA-Compatible, 75×75(mm)

AO-AO-1000