

AX-7

LCD DISPLAY

7" LCD CUSTOMER
DISPLAY MONITOR

AON
BUSINESS



- BRIGHT AND CLEAR 7" INCH CUSTOMER DISPLAY LCD SCREEN
- ADJUSTABLE HEIGHT BRACKET
- VESA STANDARD (EASILY ATTACHABLE TO ALLMAX TERMINALS)
- 800*480 RESOLUTION
- USB & RS-232 (SERIAL) PORTS



The **AX-7** LCD 7" Customer Display Monitor comes with a pole that can be customized at several lengths, providing users with an array of placement options. In addition, the monitor can be easily attached behind the ALLMAX Series All-In-One Terminals. Whether you need to display advertisement campaigns or simply provide your customers with information such as order details, the AX-7 is the solution for you

SPECIFICATION

PART NO.	AO-MO-1001	
	Display Method	TFT-LCD Display (7 inch Color Panel)
	Pattern	20columns*2 lines/20columns*4 lines
	Brightness	≥350 cd/m2
	Resolution	800*480
	character font	40*80 dot matrix
	character type	95 Alphanumeric, 32 international characters
GENERAL	character size	11.2(H)*7.29(W)mm
	Dot size(X*Y)	0.1927(H)*0.179(V)mm
	Display area	154(L)*86(W)mm
	Pole Dimension	Per support length:260(L)*35(Dia)mm/180(L)*100(W)*40(H)mm
	Base Dimension	180(W)*100(D)*40(H)mm
	Viewing Angle	Max 135°
	Horizontal Rotation	Max 355°
	Weight	1112 grams
COMMANDS MODE	15 Kinds, E.g LD220, EPSON POS D101, AEDEX, UTC/S, UTC/P, ADM788, DSP800, CD5220, EMAX, LOGIC CONTROL.	
LANGUAGE SUPPORT	CP437, Katskana, CP850, CP860, CP863, CP865, WCP1252, CP857, WCP1250, WCP1253, WCP1255, WCP1251, CP866, CP852, CP737, CP858, CP864, WCP1257, WCP1258, Tai(CP874), CP936.	
INTERFACE	RS-232 (serial)/ USB	
CONNECTION	Baud	Direct connection 9600 or 19200 bps
RELIABILITY	MTBF	30000 hours
POWER	Consumption	5-24 VDC
SAFETY	EMC standards Safety standards	FCC, CE, ROHS



Maximum Height: 52.5cm



Minimum Height: 23cm

