



AO-PR-1009

PR-1009

MOBILE RECEIPT
PRINTER 72MM,
(USB + BLUETOOTH),
70MM/S



SUPPORTS QR CODE

2000MAH BATTERY

SUPPORTS 80MM THERMAL
PRINTING

SUPPORTS MISSING PAPER
ALARM FUNCTION

**MPR-300
PR-1009
Mobile Receipt
Printer 72MM,
(USB+BLUETOOTH),
70MM/S**

MOBILE RECEIPT PRINTER

Model:	MPR-300 PR-1009
Printing Method:	Direct Thermal
Resolution:	203 DPI
Line Spacing:	3.75mm (Adjust able by commands)
Print Width:	72 mm
Max. Print Speed:	Max. 70mm/s
Media Roll Diameter:	Max. 50mm
Interfaces:	USB+Bluetooth (1+1)
Input Buffer:	128Kbytes
NV Flash:	4m Kbytes
Emulation:	ESC/POS
Character Size:	ANK, Font A: 1.5x3.0mm (12x24 dots) Font B: 1.1x2.1mm (9x17 dots) simplified tradicional Chinese: 3.0x3.0mm (24x24 dots)
Bar Code Types:	1D:UPC-A / UPC-E / JAN13 (EAN13) / JAN8(EAN8) CODE39 / ITF / CODAB AR CODE93 / CODE128 2D: QR CODE
Extended Character Sheet:	PC347(Standard Europe) / Katakana PC850(Multilingual) / PC860(Portuguese) PC863(Canadian-French) / PC865(Nordic) West Europe / Greek / Hebrew / East Europe / Iran / WPC1252 / PC866(Cyrillic#2) PC852(Latin2) / PC858 / IranII / Latvian / Arabic / PT151(1251)
Rotation:	0 ° 90 ° 180 ° 270 °
Gross Weight:	135*10 5*61.Smm (L*W*H)
Dimensions:	0 . 3kg
Printer Head Life:	50 KM
Systems:	Windows/Android/iOS/Linux
Battery:	7.4V / 2000 mAh
Charging Input:	DC 5V / 2A
Work Environment:	0 ~ 45°C, 10 ~ 80%RH no condensing
Storage Environment:	-10 ~ 60 °C . 10~90% RH no condensing



A0-PR-1009