

A0-PR-205

PR-205

Thermal Receipt
Printer 80MM,
(USB), 230MM/S



SMALL SIZE AND LOW POWER
CONSUMPTION

SUPPORT PROMPT AND ERROR
ALARM FUNCTION

SUPPORT IAP ONLINE UPGRADE

SUPPORT LINUX SYSTEM AND
OPOS DRIVER

PR-205 Thermal Receipt Printer 80MIM, (USB), 230MM/S

THERMAL RECEIPT PRINTER 80MIM, (USB), 230MM/S

Model:	Q80C
Printing Method:	Direct Thermal
Media Width:	79.5±0.5mm / 80mm
Print Width:	72mm
Column Capacity:	576 dots/line or 512 dots/line
Printing Speed:	200 mm/s
Interface:	USB (Optinal: USB+Bluetooth / USB+WIFI)
Line Spacing:	3.75 mm (Adjustable) by Commands
Character Size:	ANK, Font A: 1.5x3.0mm (12x24 dots) Font B: 1.1x2.1mm (9x17 dots)
Extension Character Sheet:	Simplified/Tradiconal Chinese:3.0x3.0mm (24x24 dots)
1D Barcode:	PC347(Standart Europe) / Katakana PC850(Multilingual) / PC860(Portugal) PC863(Canadian) / PC865(Nordic) / West Europe Greek / Hebrew East Europe / Iran/WPC1252 / PC866(Cyrilic#2) PC852(Latin2) / PC858 / Iran II Latvian / Arabic / PT151(1251) UPC-A/UPC-E/JAN13(EAN13)/JAN(EAN8)/CODE39 ITF/CODABAR/CODE93/CODE128
2D Barcode:	QR CODE
Input Buffer:	64 Kbytes/ / 56 Kbytes
NV Flash:	256 Kbytes
Power Adapter:	Input: AC 100 ~ 240V, 50 ~ 60Hz
Printer Input:	DC 24V/2.5A
Cash Drawer:	DC 24V/1A
Weight:	0.78KG
Dimensions:	166*126.5*128mm(D*W*H)
Works Environment:	Temperature (0 ~ 45°C) Humidity (10 ~ 80%)
Storage Environment:	Temperature (-10 ~ 60°C) Humidity (10 ~ 90%)
Auto Cutter:	Partial
Cutter Life:	1.5 Million Cuts
Printer Head Life:	150Km
Emulation:	ESC/POS
Driver:	Windows/Linux/macOS/Android

A0-PR-205