TouchMax-112 TOUCH SCREEN **MONITOR**

A0-M0-1004





- TFT touch screen
- 1024 X 768
- I/O: 1 x D-sub15 VGA, HDMI/USB, 1 x 12V DC in, 1 x USB(Touch Screen)

VESA Mount





SUPERIOR TOURS DI

With a 12.1" TFT LCD panel and a resolution of up to 1024 x 768 pixels, the TouchMax-112 delivers an impressive vivid and clear image. ass leading production quality provides fast and accurate touch response. Furthermore, power consumption

AOC

option is included.

VERSATILE SOLUTION

The TouchMax-112 installation guide, removable base stand and mounting options supported by VESA standard make the installation process easy and flexible. You can easily mount on a wall, counter, shelf or a pod. In addition, the TouchMax-112 is perfectly suited to meet a variety of POS and interactive solutions (Point-of-Sale, Kiosk for Point-of-Information, and digital signage).

LCD Display 12.1" TFT Panel Pixel Pitch 0.3075(H) x 0.3075(V) Max. Resolution 1024 x 768 Touch Screen Projectiive capacitive USB interface Contrast Ratio 800:1 Brightness Max.450 nits Display Color 16.2M / 262K colors OSD(On Screen Display) Power, Menu, Up, Down, Return 1/0 Port 1 x D-sub15 VGA / HDMI / USB, 1 x 12V DC in, 1 x USB(Touch Screen) Wall Mount & VESA 75*75mm Available Power Supply AC 100~240V, DC 12V / 3A Viewing Angle 80°(H), -60°-80°(V) Material Front: Bezel Zero, Back Cover: Plastic Color Black Physical Dimensions 305*133*285 mm Weight 2.56KG Temperature Operating Temp: -5° C ~ +60° C, Storage Temp: -15° C ~ +75° C Humidity Operating Humidity: 15%~85%, Storage Humidity: 15%~85%, Storage Humidity: 15%~85% Certification CE,FCC, RoHS	MODEL:	TouchMax-112 Touch Screen Monitor
Touch Screen Projectiive capacitive USB interface Contrast Ratio 800:1 Brightness Max.450 nits Display Color 16.2M / 262K colors OSD(On Screen Display) Power, Menu, Up, Down, Return 1/0 Port 1 x D-sub15 VGA / HDMI / USB, 1 x 12V DC in, 1 x USB(Touch Screen) Wall Mount & VESA 75*75mm Available Power Supply AC 100~240V, DC 12V / 3A Viewing Angle 80°(H), -60°-80°(V) Material Front: Bezel Zero, Back Cover: Plastic Color Black Physical Dimensions 305*133*285 mm Weight 2.56KG Temperature Operating Temp: -5° C ~ +60° C, Storage Temp: -15° C ~ +75° C Humidity Operating Humidity: 15%~85%, Storage Humidity: 15%~85%,	LCD Display	12.1" TFT Panel
Touch Screen Projectiive capacitive USB interface Contrast Ratio 800:1 Brightness Max.450 nits Display Color 16.2M / 262K colors OSD(On Screen Display) Power, Menu, Up, Down, Return 1/0 Port 1 x D-sub15 VGA / HDMI / USB, 1 x 12V DC in, 1 x USB(Touch Screen) VESA Yount Wall Mount & VESA 75*75mm Available Power Supply AC 100~240V, DC 12V / 3A Viewing Angle 80°(H), -60°-80°(V) Material Front: Bezel Zero, Back Cover: Plastic Color Black Physical Dimensions 305*133*285 mm Weight 2.56KG Temperature Operating Temp: -5° C ~ +60° C, Storage Temp: -15° C ~ +75° C Humidity Operating Humidity: 15%~85%, Storage Humidity: 15%~85%,	Pixel Pitch	0.3075(H) x 0.3075(V)
Contrast Ratio 800:1 Brightness Max.450 nits Display Color 16.2M / 262K colors OSD(On Screen Display) Power, Menu, Up, Down, Return 1/0 Port 1 x D-sub15 VGA / HDMI / USB, 1 x 12V DC in, 1 x USB(Touch Screen) Wall Mount & VESA 75*75mm Available Power Supply AC 100~240V, DC 12V / 3A Viewing Angle 80°(H), -60°-80°(V) Material Front: Bezel Zero, Back Cover: Plastic Color Black Physical Dimensions 305*133*285 mm Weight 2.56KG Temperature Operating Temp: -5° C ~ +60° C, Storage Temp: -15° C ~ +75° C Humidity Operating Humidity: 15%~85%, Storage Humidity: 15%~85%	Max. Resolution	1024 x 768
Brightness Max.450 nits Display Color 16.2M / 262K colors OSD(On Screen Display) Power, Menu, Up, Down, Return 1/0 Port 1 x D-sub15 VGA / HDMI / USB, 1 x 12V DC in, 1 x USB(Touch Screen) VESA Jount Wall Mount & VESA 75*75mm Available Power Supply AC 100~240V, DC 12V / 3A Viewing Angle 80°(H), -60°-80°(V) Material Front: Bezel Zero, Back Cover: Plastic Color Black Physical Dimensions 305*133*285 mm Weight 2.56KG Temperature Operating Temp: -5° C ~ +60° C, Storage Temp: -15° C ~ +75° C Humidity Operating Humidity: 15%~85%, Storage Humidity: 15%~85%,	Touch Screen	Projectiive capacitive USB interface
Display Color OSD(On Screen Display) Power, Menu, Up, Down, Return 1/0 Port 1 x D-sub15 VGA / HDMI / USB, 1 x 12V DC in, 1 x USB(Touch Screen) WESA Mount Wall Mount & VESA 75*75mm Available Power Supply AC 100~240V, DC 12V / 3A Viewing Angle 80°(H), -60°-80°(V) Material Front: Bezel Zero, Back Cover: Plastic Color Black Physical Dimensions 305*133*285 mm Weight 2.56KG Temperature Operating Temp: -5° C ~ +60° C, Storage Temp: -15° C ~ +75° C Humidity Operating Humidity: 15%~85%, Storage Humidity: 15%~85%, Storage Humidity: 15%~85%	Contrast Ratio	800:1
OSD(On Screen Display) Power, Menu, Up, Down, Return 1/0 Port 1 x D-sub15 VGA / HDMI / USB, 1 x 12V DC in, 1 x USB(Touch Screen) WESA Mount Wall Mount & VESA 75*75mm Available Power Supply AC 100~240V, DC 12V / 3A Viewing Angle 80°(H), -60°-80°(V) Material Front: Bezel Zero, Back Cover: Plastic Color Black Physical Dimensions 305*133*285 mm Weight 2.56KG Temperature Operating Temp: -5° C ~ +60° C, Storage Temp: -15° C ~ +75° C Humidity Operating Humidity: 15%~85%, Storage Humidity: 15%~85%	Brightness	Max.450 nits
1/0 Port 1 x D-sub15 VGA / HDMI / USB, 1 x 12V DC in, 1 x USB(Touch Screen) Wall Mount & VESA 75*75mm Available Power Supply AC 100~240V, DC 12V / 3A Viewing Angle 80°(H), -60°-80°(V) Material Front: Bezel Zero, Back Cover: Plastic Color Black Physical Dimensions 305*133*285 mm Weight 2.56KG Temperature Operating Temp: -5° C ~ +60° C, Storage Temp: -15° C ~ + 75° C Humidity Operating Humidity: 15%~85%, Storage Humidity: 15%~85%,	Display Color	16.2M / 262K colors
1 x USB(Touch Screen) Wall Mount & VESA 75*75mm Available Power Supply AC 100~240V, DC 12V / 3A Viewing Angle 80°(H), -60°-80°(V) Material Front: Bezel Zero, Back Cover: Plastic Color Black Physical Dimensions 305*133*285 mm Weight 2.56KG Temperature Operating Temp: -5° C ~ +60° C, Storage Temp: -15° C ~ + 75° C Humidity Operating Humidity: 15%~85%, Storage Humidity: 15%~85%	OSD(On Screen Display)	Power, Menu, Up, Down, Return
Power Supply AC 100~240V, DC 12V / 3A Viewing Angle 80°(H), -60°-80°(V) Material Front: Bezel Zero, Back Cover: Plastic Color Black Physical Dimensions 305*133*285 mm Weight 2.56KG Temperature Operating Temp: -5° C ~ +60° C, Storage Temp: -15° C ~ +75° C Humidity Operating Humidity: 15%~85%, Storage Humidity: 15%~85%	1/0 Port	
Viewing Angle80°(H), -60°-80°(V)MaterialFront: Bezel Zero, Back Cover: PlasticColorBlackPhysical Dimensions305*133*285 mmWeight2.56KGTemperatureOperating Temp: -5° C ~ +60° C, Storage Temp: -15° C ~ + 75° CHumidityOperating Humidity: 15%~85%, Storage Humidity: 15%~85%	VESA Mount	Wall Mount & VESA 75*75mm Available
Material Front: Bezel Zero, Back Cover: Plastic Color Black Physical Dimensions 305*133*285 mm Weight 2.56KG Temperature Operating Temp: -5° C ~ +60° C, Storage Temp: -15° C ~ + 75° C Humidity Operating Humidity: 15%~85%, Storage Humidity: 15%~85%	Power Supply	AC 100~240V, DC 12V / 3A
Color Black Physical Dimensions 305*133*285 mm Veight 2.56KG Temperature Operating Temp: -5° C ~ +60° C, Storage Temp: -15° C ~ + 75° C Humidity Operating Humidity: 15%~85%, Storage Humidity: 15%~85%	Viewing Angle	80°(H), -60°-80°(V)
Physical Dimensions 305*133*285 mm Weight 2.56KG Temperature Operating Temp: -5° C ~ +60° C, Storage Temp: -15° C ~ + 75° C Humidity Operating Humidity: 15%~85%, Storage Humidity: 15%~85%	Material	Front: Bezel Zero, Back Cover: Plastic
Weight 2.56KG Temperature Operating Temp: -5° C ~ +60° C, Storage Temp: -15° C ~ + 75° C Humidity Operating Humidity: 15%~85%, Storage Humidity: 15%~85%	Color	Black
Temperature Operating Temp: -5° C ~ +60° C, Storage Temp: -15° C ~ + 75° C Humidity Operating Humidity: 15%~85%, Storage Humidity: 15%~85%	Physical Dimensions	305*133*285 mm
Storage Temp: -15° C ~ + 75° C Humidity Operating Humidity: 15%~85%, Storage Humidity: 15%~85%	Weight	2.56KG
Storage Humidity: 15%~85%	Temperature	Operating Temp: -5° C ~ +60° C, Storage Temp: -15° C ~ + 75° C
Certification CE,FCC, RoHS	Humidity	
	Certification	CE,FCC, RoHS

What's in the box?







Lv152

Adapter

Power Cord