



AO-PV-1013

# SERVEPOINT 150W

## Professional All-in-One Terminal

POWER-EFFICIENT PERFORMANCE

COMPACT & DURABLE DESIGN

VIBRANT 10.1" IPS TOUCH DISPLAY

HIGH-PERFORMANCE BARCODE SCANNER

WIDE SCAN RANGE & ANGLES

ROBUST CONNECTIVITY OPTIONS

INDUSTRIAL-GRADE TEMPERATURE RESISTANCE

OPTIONAL WIRELESS FEATURES



# SERVEPOINT 150W

# Professional All-in-One Terminal



Processor	Intel® Celeron® J6412, Quad-core, clock speed 2.00 GHz, up to 2.60GHz, TDP 10W
Memory	4GB, DDR3
Storage	128GB SSD
OS	Windows 10 Pro INSTALLED
<b>DISPLAY</b>	
Type	10.1" IPS Display
Resolution	1280*800
Touchscreen	Projective Capacitive Touch Screen
<b>INTERFACE</b>	
Display	1*HDMI
USB	3*USB2.0; 1* USB3.0
Serial	1*DB9 RS232 COM
LAN	1*Gigabit Ethernet, RJ45
Audio	1*3.5mm Audio Jack
Power DC-IN	Input AC 100~240V/50~60hz, Output DC12V/5A
<b>POWER</b>	
Power Supply	Adaptor 12V, 5A
<b>SCANNER</b>	
Image Sensor	640*480 CMOS
Illumination	White LED
Aiming	Red LED(625nm)
Data Capture	All major 1D symbologies, including Code 128, EAN-13, EAN-8, Code 39, UPC-A, UPC-E, Codabar, Interleaved 2 of 5, ITF-6, ITF-14, ISBN, ISSN, Code 93, UCC/EAN-128, GS1 Databar, Matrix 2 of 5, Code 11, Industrial 2 of 5, Standard 2 of 5, AIM128, Plessey, MSI-Plessey; All major 2D symbologies, including PDF417, QR Code, Micro QR, Data Matrix
Resolution	≥3mil
Typical Depth of Field	EAN-13 : 60mm-350mm (13mil) Code 39 : 40mm-150mm (5mil) PDF417 : 50mm-125mm (6.7mil) Data Matrix : 45mm-120mm (10mil) QR Code : 30mm-170mm (15mil)
Scan Angle	Roll: 360°, Pitch: ±60°, Skew: ±60°
Min.Symbol Contrast	25%
Field of View	Horizontal 42°, Vertical 31.5°
<b>PHYSICAL&amp;ENVIRONMENTAL</b>	
Operating Temperature	Operating -20~70°
Operating Temperature	Storage -25°~75°
Dimensions(W×H×D)	251 x 288 x 49(mm)
Net Weight	1.00KG
Color	Black
VESA	75*75mm
<b>Built-in Functions</b>	
WIFI	Mini PCIe for Wireless LAN(Optional)
Bluetooth	Bluetooth 4.0(Optional)
Speaker	2*1W(Optional)

AO-PV-1013