

More Efficient , More Compacted

AO-PR-3260UEW

- Incoming Receipt Reminder
- 260mm/s High Speed
- Automatically Obtain IP Address



⊙ Top/Front paper loading/exit

⊙ Anti-insect function

⊙ Incoming/uncollected order reminder

⊙ Paper width: 80mm×φ80mm

⊙ Full or partial cut

⊙ Multi interfaces for choice



AO-PR-3260UEW Printer Technical Specifications

Printing Method	Thermal Line
Printing Resolution	8 dots/mm (203dpi), 576dots/line
Printing Speed	260mm/s (Max)
Effective Printing Width	72mm/48mm
Paper Width	79.5/57.5±0.5mm
Custom Characters	Support
Graphic Printing	Supports bitmap printing with different densities and downloadable graphics printing
Fonts	ASCII: 12×24 dots, 24×24 dots, 9×17 dots
Barcode	1D: UPCA, EAN-13, EAN-8, CODE39, ITF25, CODABAR, CODE93, CODE128
	2D: PDF417, QRCODE, Data Matrix
Interface	USB+LAN+WIFI
Supported Functions	Paper pick-up detection/ Incoming receipt reminder/Anti-insect/Buzzer/Open/Close Cover
	Alert/Paper-Out Alert/Overheat Protection/DHCP
Power Supply	DC24V ± 5%, 1.5A; Power Adapter:China Standard / EU Standard / US Standard / UK Standard
Paper Type	Normal Thermal Paper, 79.5/57.5*φ83mm(MAX)
Paper Thickness	0.06mm~0.08mm
Paper Loading Method	Easy Paper Loading
Paper Output Direction	Top/Front Paper Output
Paper Cutting Method	Auto Cut (Partial Cut)
Physical Dimensions	126.5mm × 120mm × 128mm (L × W × H)
Weight	800g (without paper roll)
Command	ESC/POS
OS Compatibility	Windows / Android / Linux / Mac /IOS
Environmental Requirements	Operating Temperature: 0°C to 50°C (32°F to 122°F)
	Operating Humidity: 10% ~ 85% RH
	Storage Temperature: -20°C to 60°C (-4°F to 140°F)
	Storage Humidity: 10% ~ 90% RH
Print Head/Cutter Life	150km / 1,500,000 cuts

Application Scenarios



Cashier



Kitchen



Retail



Beverages



Takeout

